

Rede electrosoldada (Malha sol)

Designação			Diâmetro		Distância entre eixos dos varões		Peso da armadura
			Longitudinal mm	Transversal mm	Longitudinal mm	Transversal mm	Kg/m²
Superfície lisa	Malha 300x100	MR 30	3,0	3,0	100	300	0,74
		MR 34	3,4	3,4			0,95
		MR 38	3,8	3,8			1,19
	Malha 100x100	AQ 30	3,0	3,0	100	100	1,10
		AQ 38	3,8	3,8			1,77
	Malha 150x150	CQ 30	3,0	3,0	150	150	0,74
CQ 38		3,8	3,8	1,19			
Superfície nervurada	Malha 300x100	NR 40	4,0	4,0	100	300	1,32
		NR 45	4,5	4,0			1,58
		NR 50	5,0	5,0			2,06
		NR 55	5,5	5,0			2,38
		NR 60	6,0	5,0			2,73
		NR 65	6,5	5,0			3,12
		NR 70	7,0	5,5			3,65
		NR 75	7,5	6,0			4,21
		NR 80	8,0	6,5			4,81
		NR 85	8,5	6,5			5,32
		NR 90	9,0	7,0			6,00
		NR 100	10,0	7,5			7,32
	NR 120	12,0	10,0	10,93			
	Malha 100x100	AQ 40	4,0	4,0	100	100	1,98
		AQ 45	4,5	4,5			2,50
		AQ 50	5,0	5,0			3,08
		AQ 60	6,0	6,0			4,44
		AQ 70	7,0	7,0			6,04
		AQ 80	8,0	8,0			7,90
		AQ 90	9,0	9,0			9,98
		AQ 100	10,0	10,0			12,34
		AQ 120	12,0	12,0			17,76
	Malha 150x150	CQ 40	4,0	4,0	150	150	1,32
		CQ 45	4,5	4,5			1,66
		CQ 50	5,0	5,0			2,06
		CQ 60	6,0	6,0			2,96
		CQ 70	7,0	7,0			4,02
CQ 80		8,0	8,0	5,26			
CQ 90		9,0	9,0	6,66			
CQ 100		10,0	10,0	8,22			
CQ 120		12,0	12,0	11,84			

Dimensões standard:

Painéis: 6,00m x 2,40m

Rolos: 50,00m x 2,40m

Obs.: Medidas standard. Outras medidas e/ou qualidades, sob consulta.